Supplied with 4 m 2 core FEP cable

NTC Temperature Sensor -50 °C to +70 °C

## DATAssure™ D3

FTEP3-DS302-HR

## For use with the DATAssure™ D3 family of wireless base stations. Compatible with a full range of Intelligent Wireless Transmitters (supplied separately).

A general purpose temperature sensor for measuring air and contact temperature over the range of -50 °C to +70 °C. The sensor utilises a NTC thermistor which offers excellent stability and low drift over the lifetime of the sensor. The thermistor is housed within a 6 mm diameter 316 L grade stainless steel housing back filled with epoxy with a heat shrink sheath. The FEP cable allows the cable to flex over its full operating range. The probe is supplied with a 4 m cable. Common uses: Fridges | Freezers | Cold Rooms | Production Areas | Chilled & Cold Pipework

This product can be supplied with a calibration certificate.

Technical Specification

Temperature Range: -50 °C to +70 °C

Accuracy:

Below -30 ° -30 °C to +70 °C

Standard - ±0.8 °C ±0.5 °C

Calibrated - ±0.5 °C ±0.2 °C

**Thermistor:** NTC 5K R/T curve 8016/A01 **Weight:** 80 g

Sensor Cable: 4000 mm 2 core FEP cable Probe Sheathing: 316 L grade stainless steel

On Cable Electronics

Connector IP Rating: IP67

Connector: 3 pin male Hirose
Operating Temperature: -20 °C to +55 °C
Electronics Sheathing: Technomelt OM678

**Electronics & Probe** 

IP Rating: IP68

## Compatible FTEP2-WS Wireless Transmitters

Part No. Description

FTEP2-WS102-0433 Single Input Wireless Transmitter with Hirose Connector (433 Mhz)
FTEP2-WS103-0433 Dual Input Wireless Transmitter with Hirose Connectors (433 Mhz)
FTEP2-WS102-2400 Single Input Wireless Transmitter with Hirose Connector (2.4 Ghz)
Dual Input Wireless Transmitter with Hirose Connectors (2.4 Ghz)

**Tel:** +44 (0)1932 755 000

**Fax:** +44 (0)1932 755 001

## **Compatible Accessories**

FTEP7-SA1009 Probe Fixing Bracket (for pipework, etc)

Ci067/V2

