Supplied with 4 m 3 core FEP cable

PT1000 Temperature Sensor -45 °C to +100 °C

DATAssure™ D3

FTEP3-DS307-HR

For use with the DATAssure™ D3 family of wireless base stations. Compatible with a full range of Intelligent Wireless Transmitters (supplied separately).

A general purpose temperature probe for measuring air and contact temperature over the range of -45 °C to +100 °C. A Class B PT100 sensor element is housed within a 6 mm 316 L stainless steel diameter housing back filled with epoxy with a heat shrink sheath. The FEP cable allows the cable to flex over its full operating range. Supplied with a 4 m cable. Common uses: Fridges | Freezers | Cold Rooms | Production Areas | Hot & Cold Pipework

This product can be supplied with a calibration certificate.

Technical Specification

Temperature Range: -45 °C to +100 °C

Accuracy:

	Below -20 °	-20 ° to +70 °C	70 ° to +100 °C
Standard	±1.0 °C	±0.5 °C	±1.2 °C
Calibrated	±0.5 °C	±0.2 °C	±0.5 °C

Thermistor: PT100 Class B

Weight: 80 g

Sensor Cable: 4000 mm 3 core FEP cable Probe Sheathing: 316 L grade stainless steel

On Cable Electronics

Connector IP Rating: IP67

Connector: 3 pin male Hirose
Operating Temperature: -20 °C to +55 °C
Electronics Sheathing: Technomelt OM678

Electronics & Probe

IP Rating: IP68

Compatible FTEP2-WS Wireless Transmitters

Part No. Description

FTEP2-WS102-0433 Single Input Wireless Transmitter with Hirose Connector (433 Mhz)
FTEP2-WS103-0433 Dual Input Wireless Transmitter with Hirose Connectors (433 Mhz)
FTEP2-WS102-2400 Single Input Wireless Transmitter with Hirose Connector (2.4 Ghz)
FTEP2-WS103-2400 Dual Input Wireless Transmitter with Hirose Connectors (2.4 Ghz)

Tel: +44 (0)1932 755 000

Fax: +44 (0)1932 755 001

Compatible Accessories

FTEP7-SA1009 Probe Fixing Bracket (for pipework, etc)

Ci072/V2

