



Battery Backup

550 VA Single Phase

- Maximum compactness
- USB interface
- Short-circuit protection
- 2 Year warranty
- User replaceable batteries



This UPS is designed to provide at least 30 minutes of 'battery supply' to our DATAcentre & Auto-dialer to ensure you can get the alarm even if you have no power. The system will continue to work as if it still has power. If you require a monitor to log or alert you when there is a power failure please contact Planer.

The compactness, versatility (a push-button switch with LED-based mimic panel and user-replaceable batteries) and functionality allow it to easily fit into your lab. When mains fails, connected loads are powered with a pseudo sine wave supply from the inverter and battery supply.

Features

- 3 sockets with mains fail protection
- 1 socket without mains fail protection for powering loads such as laser printers
- Integrated protection for telephone line/modem
- Cold start capability: the UPS can power up without a mains supply present
- User replaceable batteries
- Can be placed on desktop, floor, or be wall-mounted
- Input supply and telephone cable included
- Auto restart (on mains return, after batteries have discharged)
- GS/TUV marks

| Technical Specifications | |
|---------------------------------|--|
| POWER | 550VA/335W |
| INPUT | |
| Rated voltage | 230 Vac |
| Voltage range | 188-262 Vac |
| Frequency | 50/60 Hz |
| OUTPUT | |
| Voltage on mains operation | 230 Vac |
| Frequency on battery operation | 50/60 Hz |
| Waveform from battery/inverter | Pseudo sinewave |
| BATTERIES | |
| Type | Maintenance free sealed lead-acid |
| Recharge time | 6-8 h |
| ENVIRONMENTAL | |
| Tel. Protection | RJ45 connectors |
| Communication | On USB interface |
| Safety compliance | EN 50091-1-1 and Directives 73/23 EEC, 93/68 EEC |
| EMC conformance | EN 50091-2 cl. B and Directives 89/336 EEC, 92/31 EEC, 93/68 EEC |
| Marks | CE; GS/TUV |
| Operating temperature | 0 - 40°C |
| Colour | Graphite grey |
| Elevation and relative humidity | 6000 meters max, elevation, 0-90% non condensing |
| Accessories provided | 1 input supply cable, telephone cable |
| Weight (kg) | 3.1 |
| Dimensions (hwd) (mm) | 88 x 120 x 320 |