



Pulse Counting Sensor

DATAssure™ D3

FTEP3-DS318-HR

For use with the DATAssure™ D3 family of wireless base stations. Compatible with a full range of Intelligent Wireless Transmitters (supplied separately).

Connects to any industry standard pulsed output meter with a standard pulse length of 100 ms. The signal can then be converted via a user custom table to a measured value for monitoring and alarm purposes.

Common uses: Measurement energy consumption | Measurement of liquids and gases flow.

Technical Specification		On Cable Electronics	
Input Range:	External volt free signal contact	Connector IP Rating:	IP67
Pulse Length:	Min >50 ms	Connector:	3 pin male Hirose
Pulse Interval:	Min >50 ms	Operating Temperature:	-20 °C to +55 °C
Weight:	38g	Electronics Sheathing:	Technomelt OM678
Sensor Cable:	1500mm 2 Core Arctic Cable	Electronics IP Rating:	IP68

Compatible FTEP2-WS Wireless Transmitters

Part No.	Description
FTEP2-WS102-0433	Single Input Wireless Transmitter with Hirose Connector (433 Mhz)
FTEP2-WS103-0433	Dual Input Wireless Transmitter with Hirose Connectors (433 Mhz)
FTEP2-WS102-2400	Single Input Wireless Transmitter with Hirose Connector (2.4 Ghz)
FTEP2-WS103-2400	Dual Input Wireless Transmitter with Hirose Connectors (2.4 Ghz)

Compatible Accessories

FTEP7-SA1010	Intelligent Sensor Extension Cable - 4 Meters
--------------	---